

Listing of the Claims:

1. (Amended) A hub for use in conjunction with a spool having a quantity of material wrapped thereon, the material having a number of known characteristics, the hub comprising:

- a core including a central axis;
- the core being structured to be disposed on the spool;
- an indication member;
- the indication member including a support and at least a first tab, and a second tab;
- the at least first tab being an at least first home tab and defining a home position of the indication member;
- the second tab being a characteristic tab;
- the support being mounted on the core;
- the at least first tab and second tabs being disposed on the support; and
- the at least first tab and second tabs each including an elongated dimension that extends in a generally radial direction with respect to the central axis of the core;
- the second tab being oriented at one of a plurality of known angles with respect to the at least first home tab; and
- the orientation of the second tab with respect to the at least first home tab corresponding with the characteristics of the material.

2. (Original) The hub of Claim 1,
wherein the indication member is generally flat; and
the support and the at least first tab being generally coplanar.

3. (Amended) The hub of Claim 1,
wherein the indication member ~~further includes a second tab;~~
~~the second tab having an elongated dimension that extends in a generally radial direction with respect to the central axis of the core; and~~
~~the indication member being~~ is a monolithically-formed single-piece member.

4. (Original) The hub of Claim 3,
wherein the support extends between the at least first and second tabs;
the support being at least partially arcuate.
5. (Original) The hub of Claim 1,
wherein the support is an elongated arcuate member; and
the at least first tab extending generally perpendicularly away from the support.
6. (Original) The hub of Claim 1,
wherein the at least first tab extends from the support in a direction generally away from
the central axis.
7. (Original) The hub of Claim 1,
wherein the at least first tab extends from the support in a direction generally toward the
central axis.
8. (Original) The hub of Claim 1,
wherein the support is generally ring-shaped.
9. (Amended) The hub of Claim 1,
wherein ~~the indication member further includes a second tab;~~
~~the second tab having an elongated dimension that extends in a generally radial direction~~
~~with respect to the central axis of the core;~~
the support ~~including~~ includes a first support portion and a second support portion that
are separated from one another;
the at least first tab being disposed on and extending from the first support portion; and
the second tab being disposed on and extending from the second support portion.
10. (Original) The hub of Claim 1,
wherein the support is substantially embedded in the core.

11. (Amended) [The hub of Claim 10,] A hub for use in conjunction with a spool, the hub comprising:

a core including a central axis;

the core being structured to be disposed on the spool;

an indication member;

the indication member including a support and at least a first tab;

the support being mounted on the core;

the at least first tab being disposed on the support; and

the at least first tab including an elongated dimension that extends in a generally radial direction with respect to the central axis of the core

the support being substantially embedded in the core;

wherein the at least first tab is substantially embedded in the core;

a window is formed in the core; and

the window extending between the at least first tab and the exterior of the core.

12. (Original) The hub of Claim 1,
wherein the indication member is at least partially metallic.

13. (Amended) A hub for use in conjunction with a spool having a quantity of material wrapped thereon, the material having a number of known characteristics, the hub comprising:

a core having a central axis and being structured to be disposed on the spool; and

an indication member;

the indication member including a support ~~and~~ , at least a first tab, and a second tab;

the at least first tab being an at least first home tab and defining a home position of the indication member;

the second tab being a characteristic tab;

the support being mounted on the core;

the at least first ~~tab~~ and second tabs being disposed on the support;

the at least first and second tabs each including an elongated dimension that extends in a generally radial direction with respect to the central axis of the core;

the second tab being oriented at one of a plurality of known angles with respect to the at least first home tab; and

the orientation of the second tab with respect to the at least first home tab corresponding with the characteristics of the material; and

the support ~~and~~, the at least first tab, and the second tab each being of a generally planar configuration.

14. (Amended) The hub of Claim 13,
wherein the support ~~and~~, the at least first tab, and the second tab are generally coplanar.

15. (Amended) The hub of Claim 13,
wherein the core ~~includes a central axis; and~~
~~the at least first tab including an elongated dimension that extends in a generally radial direction with respect to~~ is structured to be rotated about the central axis, the rotational distance between the home position and the second tab corresponding with the characteristics of the material.

16. (Amended) The hub of Claim 15,
wherein ~~the indication member further includes a second tab;~~
~~the second tab having an elongated dimension that extends in a generally radial direction with respect to the central axis of the core; and~~
the indication member ~~being~~ is a monolithically-formed single-piece member.

17. (Original) The hub of Claim 16,
wherein the support extends between the at least first and second tabs;
the support being at least partially arcuate.

18. (Original) The hub of Claim 15,
wherein the at least first tab extends from the support in a direction generally away from the central axis.

19. (Original) The hub of Claim 15,
wherein the at least first tab extends from the support in a direction generally toward the central axis.

20. (Original) The hub of Claim 13,
wherein the support is an elongated arcuate member; and
wherein the at least first tab extends generally perpendicularly away from the support.

21. (Original) The hub of Claim 13,
wherein the support is generally ring-shaped.

22. (Amended) The hub of Claim 13,
~~wherein the indication member further includes a second tab;~~
~~the second tab having an elongated dimension that extends in a generally radial direction~~
~~with respect to the central axis of the core;~~
the support ~~including~~ includes a first support portion and a second support portion that
are separated from one another;
the at least first tab being disposed on and extending from the first support portion; and
the second tab being disposed on and extending from the second support portion.

23. (Original) The hub of Claim 13,
wherein the support is substantially embedded in the core.

24. (Amended) [The hub of Claim 13,] A hub for use in conjunction with a spool,
the hub comprising:
a core structured to be disposed on the spool; and
an indication member;
the indication member including a support and at least a first tab;
the support being mounted on the core;
the at least first tab being disposed on the support;
the support and the at least first tab each being of a generally planar configuration;

wherein the at least first tab is substantially embedded in the core;
a window being formed in the core; and
the window extending between the at least first tab and the exterior of the core.

25. (Original) The hub of Claim 13,
wherein the indication member is at least partially metallic.

26. (Amended) A detectable spool for use in a printer, the detectable spool comprising:

a spool including a central axis and being structured to have a quantity of material wrapped thereon, the material having a number of known characteristics;

indication means disposed on the spool;

the indication means including an indication member;

the indication member including a support and, at least a first tab, and a second tab; and

the at least first tab and second tabs each including an elongated dimension that extends in a generally radial direction with respect to the central axis;

the at least first tab being an at least first home tab and defining a home position of the indication member;

the second tab being a characteristic tab;

the second tab being oriented at one of a plurality of known angles with respect to the at least first home tab; and

the orientation of the second tab with respect to the at least first home tab corresponding with the characteristics of the material.

27. (Original) The detectable spool of Claim 26,
wherein the indication member is generally flat; and
the support and the at least first tab being generally coplanar.

28. (Amended) The detectable spool of Claim 26,
~~wherein the indication member further includes a second tab;~~

~~the second tab having an elongated dimension that extends in a generally radial direction with respect to the central axis; and~~

the indication member ~~being~~ is a monolithically-formed single-piece member.

29. (Original) The detectable spool of Claim 28,
wherein the support extends between the at least first and second tabs;
the support being at least partially arcuate.

30. (Original) The detectable spool of Claim 26,
wherein the support is an elongated arcuate member; and
the at least first tab extending generally perpendicularly away from the support.

31. (Original) The detectable spool of Claim 26,
wherein the at least first tab extends from the support in a direction generally away from
the central axis.

32. (Original) The detectable spool of Claim 26,
wherein the at least first tab extends from the support in a direction generally toward the
central axis.

33. (Original) The detectable spool of Claim 26,
wherein the support is generally ring-shaped.

34. (Amended) The detectable spool of Claim 26,
wherein ~~the indication member further includes a second tab;~~
~~the second tab having an elongated dimension that extends in a generally radial direction with respect to the central axis;~~

the support ~~including~~ includes a first support portion and a second support portion that are separated from one another;

the at least first tab being disposed on and extending from the first support portion; and
the second tab being disposed on and extending from the second support portion.

35. (Original) The detectable spool of Claim 26,
wherein the indication means further includes a core;
the support being substantially embedded in the core; and
the core being disposed on the spool.

36. (Amended) [The detectable spool of Claim 35,] A detectable spool for use in a printer, the detectable spool comprising:

a spool including a central axis;

indication means disposed on the spool;

the indication means including an indication member;

the indication member including a support and at least a first tab;

the at least first tab including an elongated dimension that extends in a generally radial direction with respect to the central axis

the indication means further including a core;

the support being substantially embedded in the core;

the core being disposed on the spool;

wherein the at least first tab is substantially embedded in the core;

a window being formed in the core; and

the window extending between the at least first tab and the exterior of the core.

37. (Original) The detectable spool of Claim 26,
wherein the indication member is at least partially metallic.

38. (Amended) A detectable spool for use in a printer, the detectable spool comprising:

a spool having a central axis and being structured to have a quantity of material wrapped thereon, the material having a number of known characteristics; and

indication means disposed on the spool;

the indication means including an indication member;

the indication member including a support and, at least a first tab, and a second tab;